



Description

WEBS-BACKUP is power reserve backup system designed to provide the WEBS-MT/R with one hour of continuous operation after twenty-three hours with no external power.

Components

- Marine / aviation grade deep cycle batteries
- Uninterruptible power supply and charging system
- Mounting shelf inside the tower for battery
- Mounting and installation hardware

Features

- An uninterruptible power supply that provides twenty-four (24) hours of battery autonomy; one (1) hour of continuous operation after twenty-three (23) hours of power failure.
- Maintenance free Absorbed Glass Mat (AGM) deep cycle battery.
- Battery operates a wide range of temperatures from -40°C (-40°F) to +72°C (+160°F).
- The battery is kept fully charged and maintains proper storage voltage.
- Provides power to the LED Blue Light, LED panel light, VOIP-500 series phone and WEBS® Paging Amplifier.

Specifications

Battery:	Quantity: 2 Dimensions: 7.71(196) L x 5.18(132) W x 8.05(204) H in(mm) Weight: 30 lbs (13.6 kg) Output Voltage: 12VDC Capacity: 42 Ah @ 25° C (77° F), 24 Hour Rate
UPS:	Dimensions: 11.00 (279) L x 6.30 (160) W x 4.72 (120) H in (mm) Weight: 4 lbs (1.8 kg) Output Voltage: 12VDC Output Current: 20 Amps Input Voltage: 120VAC, 50/60Hz
Mounting:	All components fit within the WEBS-MT/R tower or an optional external enclosure.
Compliance:	System components are recognized to UL standards.

WEBS-BACKUP WEBS-MT/R Backup Power System